



ANALYTIC SYSTEMS

Power Conversion Solutions

#207 12448 82nd Ave.
Surrey, BC V3W 3E9 CANADA

+1 (604) 543-7378 · phone
1-800-668-3884 · toll free
+1 (604) 543-7354 · fax

www.analyticsystems.com



Benefits

- Ultra-Quiet
- Power sensitive electronics without interference
- Rugged & Reliable
- Ensure years of safe and trouble free operation

Applications

- Marine / Automotive / RV
- Electric Utilities and Substations
- Telecom Power Plants
- Manufacturing Locations
- Steel Mills
- Military Applications (COTS)
- Industrial Controls
- OEM Applications
- Solar / Alternative Power Systems
- Fuel Cells

DC/AC Pure-Sine Inverters

IVS2500R Series Pure Sinewave Inverter

Description

The IVS2500R Series is a compact 2500VA 19" Rackmount DC/AC pure sinewave inverter that uses established design techniques to ensure high reliability.

Suitable for a wide range of applications, the IVS2500R features full electronic protection, high efficiency and low output noise.

The built-in fan provides sufficient airflow for operation without de-rating up to 50°C ambient temperature. Extended operating temperature (-40 to +65°C) is available.

The inverter can be loaded with a fluorescent lamp load up to the full-specified output power.

Features

- Input is filtered to EN 55022 Class B
- Very low 60Hz input ripple current
- Modular design, light weight
- Sinusoidal wave shape
- Multiple input and output voltages available
- 2500VA of output power
- Full electronic protection
- Field-proven design topology

IVS2500R Series 19" Rackmount Pure Sinewave Inverters

Specifications

Input Voltage	24V, 36V, 48V, 125V, 270VDC +/-20% are standard Other inputs available, please consult factory
Input Protection	Thermal fuse, Inrush current limiting, Reverse polarity protection
Input Isolation	Input to chassis 500VDC for <60V input – 1500VDC for >60V input Input to output 2250VDC – Output to chassis 2250VDC
Output Voltage	115VAC/60Hz /21.7A continuous with grounded neutral Isolated floating output optional (Consult factory for other voltages and frequencies)
Wave Form	Sinusoidal
Total Harmonic Distortion	Better than 5% at full load
Efficiency	Min 78% at full load
Line Regulation	Maximum 0.5%
Load Regulation	Maximum ± 6% from 10% load to full load
Output Protection	Current limiting with short circuit protection, thermal shutdown with automatic recovery in case of continuous overload or insufficient airflow
EMI / RFI Suppression	Meets EN 55022 Class B
Load Crest Factor	Maximum 3.0 at 90% load
Operating Temperature Range	0°C to +50°C
Humidity	5 - 95% non-condensing
Temperature Drift	0.05% per °C over operating temperature range
Dimensions	4U" X 19" x 15" enclosed case (H x L x W)
Connections	Input: Compression-type terminal Output: Standard AC receptacle
Weight	30 pounds (13.4 Kg)
Options	Output Fail Alarm (Form C) Remote Inhibit: by connecting DC voltage (as specified) to the inhibit terminals
Safety	Compliance to IEC950, CSA C22.2 No. 950 and UL 1950 Please contact factory for approval status for the requested input/output configuration

Warranty: Twelve months subject to application within good engineering practice

Enhancements to these general specifications can be accommodated upon request
Designed to meet common approval requirements. Specifications Subject to Change Without Notice
Designed and Manufactured in Canada

Available From:



ANALYTIC SYSTEMS
Quality since 1976

#207 12448 82nd Ave.
Surrey, BC V3W 3E9 CANADA
+1 (604) 543-7378 • phone
1-800-668-3884 • toll free
+1-604-543-7354 • fax
www.analyticssystem.com

© 2003 Analytic Systems Ware Ltd. (1993)