

RACK MOUNT POWER SUPPLIES

**100 AMPS
Battery
Back-up**

New high current switching DC power system with battery backup and charging feature provides N+1 redundancy and is expandable from 40 Amps to 100 Amps!




ASW N+1 DC POWER SYSTEM with battery backup and charging feature!

- Provides N+1 Redundancy for critical power supply applications
- 40, 60, 80 and 100 Amps models are rated for continuous output
- 40, 60 and 80 Amp models can be expanded to 100 Amps by adding Samlex 20 Amp power supply modules
- Voltage/Amperes Meter
- External Battery Connection provides uninterrupted DC power
- D-sub connector for remote analog monitoring
- Module status LEDs, fault indicator LEDs and fault alarm are standard features on all models
- Highly regulated output voltage
- Short circuit protection and over-load current limiting with automatic reset feature
- 3.5" height, 19" wide
- 1 Year Warranty



ASW SEC-1223R1 DC POWER SUPPLY

- 23 Amp switching power supply rated 100% duty cycle
- UL & cUL listed
- 3 year Warranty



ASW SEC-1223R2 DC POWER SUPPLY

- Two independent 23 Amp switching power supplies rated 100% duty cycle
- UL & cUL listed
- 3 year Warranty

— SEE BACK FOR COMPLETE SPECIFICATIONS —

S P E C I F I C A T I O N S

N+1 DC POWER SYSTEM WITH BATTERY BACKUP CHARGING FEATURE

SEC-40BRM SEC-60BRM SEC-80BRM SEC-100BRM SEC-1212R1 SEC-1223R1 SEC-1223R2

INPUT VOLTAGE

Factory Pre-set								
120 VAC Nominal	105 - 125 VAC	105 - 125 VAC	105 - 125 VAC	105 - 125 VAC	100 - 130 V	100 - 130 V	100 - 130 V	
*230 VAC Nominal	N/A	N/A	N/A	N/A	*200 - 260 V	*200 - 260 V	*200 - 260 V	

INPUT FREQUENCY

50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	
----------	----------	----------	----------	----------	----------	----------	----------	--

OUTPUT VOLTAGE

13.8 VDC	13.8 VDC	13.8 VDC	13.8 VDC	13.8 VDC	13.8 VDC	13.8 VDC	13.8 VDC	
----------	----------	----------	----------	----------	----------	----------	----------	--

TOTAL OUTPUT CURRENT

Continuous	40 Amps	60 Amps	80 Amps	100 Amps	10 Amps	23 Amps	23 Amps x 2	
Surge	46 Amps	69 Amps	92 Amps	115 Amps	12 Amps	24 Amps	24 Amps x 2	

CURRENT LIMITING

48 Amps	72 Amps	96 Amps	120 Amps	14 Amps	25 Amps	25 Amps x 2		
---------	---------	---------	----------	---------	---------	-------------	--	--

CHARGING CURRENT

————— MAX 8 Amps —————

n/a	n/a	n/a	
-----	-----	-----	--

RACKMOUNT SIZE(ins)

19 x 3.5	19 x 3.5	19 x 3.5	19 x 3.5	19 x 3.5	19 x 3.5	19 x 3.5	19 x 3.5	
----------	----------	----------	----------	----------	----------	----------	----------	--

CHASSIS

STEEL (BLACK EPOXY POWDER COAT)

ALUMINUM (BLACK ANODIZED)

COVER

STEEL (BLACK EPOXY POWDER COAT)

STEEL (BLACK EPOXY POWDER COAT)

SAFETY LISTINGS

N/A	N/A	N/A	N/A	N/A		UL & cUL		
-----	-----	-----	-----	-----	--	----------	--	--

UL FILE NUMBER

N/A	N/A	N/A	N/A	N/A		E179076		
-----	-----	-----	-----	-----	--	---------	--	--

WEIGHT

Kg.	9.3	10.0	10.7	11.2	2.0	2.2	3.7	
lbs.	20.5	22.0	23.5	25.0	4.4	4.8	8.2	

DIMENSIONS W X H X D (ins)

	19 X 3.5 X 16				19 X 3.5 X 8.7			
--	---------------	--	--	--	----------------	--	--	--

WARRANTY

1 YEAR	1 YEAR	1 YEAR	1 YEAR	1 YEAR	3 YEAR	3 YEAR	3 YEAR	
--------	--------	--------	--------	--------	--------	--------	--------	--

*Nominal input voltage can be set at 240 VAC by changing the position of a jumper located inside the unit. Read the operators manual for instructions.

FOR PERFORMANCE & VALUE CALL ANALYTIC SYSTEMS: 1-800-668-3884

Internet: <http://www.analyticssystem.com> — Email: info@analyticssystem.com